





HOME/CONTACT SPARK ARRESTERS SILENCERS EXHAUST CLEANERS ACCESSORIES CATALOGUE



AUXILIARY

Designed to be fitted at the end of the exhaust assembly alongside the silencer, the auxiliary range is ideal for short term installations or where there is limited space. The models can cover engines with an output of up to 165 HP and can also be used for permanent installations if required. It is critical when permanently installing an auxiliary range model that sufficient support is provided, please refer to the catalogue for appropriate mounting accessories.

Model	Pipe Size Range (")	Power Range (HP)	L Barrel Length (mm)	D Barrel Diameter (mm)
WT 1L 92	1.25 – 1.75	5 – 25	135	90
WT 1L 125	1.50 – 2.00	15 – 35	145	125
WT 1L 152	1.75 – 2.50	20 – 50	165	152
WT 1L 175	2.00 – 2.50	30 – 70	200	175
WT 1L 205	2.25 – 2.75	40 – 90	205	205
WT 1L 235	2.50 – 3.50	70 – 130	235	235
WT 1L 300	3.50 – 4.00	90 – 165	300	300

The data above is for reference purposes only, for full product specifications please refer to the catalogue or contact us.

SPECIFICATION

- ✓ Fully ATEX Compliant
- ✓ Supplied With Declaration of Conformity Certificate
- ✓ Stainless Steel Construction (also available in mild steel)
- ✓ Compact Design
- ✓ Easy Installation
- ✓ Can Be Mounted Horizontally or Vertically
- ✓ Compatible Mounting Hardware Available
- ✓ Inlet Pipe ID Swelled & Slotted, Outlet Pipe OD
- ✓ Supplied With Exhaust Clamps For Inlet Pipe

